


Taian zhengtai construction machinery Co., Ltd Industrial Park Shiheng town Feicheng City Shandong province China

whatsapp/ wechat: +86 13953879973 EMAIL: woniuniu9527@163.com







Description			Specification
Equipment weight		kg	21000
Dimensions	long	mm	7000
	Wide (pushing shovel)	mm	3350
	Wide (outside of the front wheel)	mm	3350
	Wide (outside of the rear wheel)	mm	3350
	high	mm	3530
Wheelbase		mm	2750
Ground clearance		mm	280
wheel	Pressure roller width (front/rear)	mm	900
	Pressure roller diameter (front/rear, out of the tooth)	mm	1600
	Pressure roller diameter (front/rear, out-of-wheel)	mm	1290
	Number of teeth (front/rear)	个	64
Motion transfer system	Engine manufacturer		WEICHAI
	${\sf model}$		WD10G220E23
	Engine power	kw	162
	Engine speed	r/mir	2000
	Electrical System	V	24
Number of driving wheels			4
speed	front I 0-4.2	km/h	
	front II km/h 0-15.7	km/h	
	rear km/h 0-5.8	km/h	
Push shovel	Pusher height	mm	1880
	Push shovel width	mm	3350
	Pusher lift height	mm	980
	Push shovel into the ground	mm	150
Braking System	Driving brake, pneumatic oil		
	Parking/emergency brake machinery, uplift brake		
steering system	Steering mode Hydraulic, central articulated, sub-pendulum swing		
	±° 40 Steering angle ±° 40		
	±° 15 Lateral swing angle ±° 15		
	Turning radius (outside of the front wheel) mm 6085		

Optional

Standard configuration ordinary axle+two-stage emission engine

Wet brake bridge+three stage emission engine